

# Portable Fire Extinguishers

## DESCRIPTION

Buckeye's 2.5 LB Sodium Bicarbonate based fire extinguisher is designed for use in combating Class B and C type fires.

Commonly known as a Standard or Regular fire extinguisher, this extinguisher is designed for use on flammable liquid fires in homes, office buildings, storage warehouses, motor vehicles, and for manufacturing processes such as painting, dipping, and coating.

## FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards and is DOT compliant. UL and ULC Listed
- Trilingual label: English, Spanish, and French
- US COAST GUARD approved as Type B:C Size I when used in conjunction with Mounting Bracket Model A2. Mounting Bracket included.
- Polyester epoxy powder coated steel cylinder with anodized all-metal valve assembly.
- Standard dry chemical is available in 50 lb. Pails for recharging Buckeye extinguishers. P/N 61400

## SPECIFICATIONS

Agent Capacity	2.5 lbs / 1.13 kg
UL/ULC Rating	10-B:C
Shipping Weight	5.5 lbs / 2.5 kg
Height	14.75 in / 37.5 cm
Width	4.875 in / 12.4 cm
Cylinder Diameter	3.375 in / 8.6 cm
Discharge Time	9 seconds
Discharge Range	9-15 ft / 2.7 - 4.6m
Operating Temperature Range	-65° F to 120° F -54° C to 49° C

## ORDERING INFORMATION

**2.5 LB STD Dry Chemical  
Fire Extinguisher with  
Vehicle Bracket**

Part No: 13415

Refer to the Buckeye Spare Parts List for replacement parts



110 Kings Road, Kings Mountain, NC 28086-0428

704-739-7415

704-739-7418

[www.buckeyef.com](http://www.buckeyef.com)